



High Yield



Fire Retardant



3X Expansion

FIREBLOCK

Titebond® WeatherMaster™ X-TREME Fireblock low pressure one-component polyurethane foam sealant is a moisture cured foam designed to seal, fill, bond and stop air infiltration in areas where a fireblock product is required. It has a recognizable orange color allowing inspectors to easily identify the use of an approved fireblock product for Type V residential construction. Due to its expansion characteristics, it is more effective than many traditional fireblocking materials for the blocking of flames and smoke in concealed penetrations, preventing flame spread from room to room and floor to floor.

- **CLASS A – FIRE RETARDANT**
- **X-TREME TEMPERATURES 0° TO 100°F**
- **BLOCKS FLAMES & SMOKE EFFECTIVELY**
- **STOPS AIR INFILTRATION**
- **MORE COST EFFECTIVE THAN STANDARD CAULKS**
- **TYPE V RESIDENTIAL FIREBLOCK WITH IDENTIFIABLE ORANGE COLOR**
- **GREENGUARD GOLD CERTIFIED**

SPECIFICATIONS

• ASTM D1622; ASTM C518; ASTM E2178; ASTM D1621; ASTM 1623; ASTM D2126; UL GREENGUARD GOLD and UL

PHYSICAL AND CHEMICAL CHARACTERISTICS:

Type: Low pressure, one-component, polyurethane foam sealant

Flashpoint: -156° F (-68.9° C), estimated based on the liquefied petroleum gas (Hydrocarbon HC)

Freeze/Thaw Stability: Stable

Reactive VOC: 165 g/L

Density – Gun Foam: 1.00 lbs/ft³ (16 kg/m³)

Density – Straw Foam: 1.10 lbs/ft³ (17.6 kg/m³)

K-Factor: 0.222 BTU · inch/ (ft² · h · °F)

R-Value: 4.50 per Inch

Air Barrier Properties: @1.57 psf (75 Pa)


Compressive Strength: 6.38 psi (43.9 kPa)

Tensile Strength: 12 psi (83 kPa)

Dimensional Stability: ± 5%

Closed-Cell Content: 77%

LIMITED WARRANTY: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



FIREBLOCK

Product #	Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet
8541	12 oz.	14 lbs./Case	037083085419	10037083085416	12	75
8542	24 oz.	24 lbs./Case	037083085426	10037083085423	12	48

APPLICATION INSTRUCTIONS

24 oz. - Dispensing Unit only application method: Shake well, attach the container to X-TREME Dispensing Unit and begin dispensing. The Dispensing Unit can be metered by pulling the trigger for the desired rate, or with the metering screw located in the back. Foam application can be interrupted when needed as outlined in the instructions and the Dispensing Unit will be ready for immediate re-use, as long as it remains attached to a pressurized container. An empty gun foam container must be replaced with a new container.

12 oz. - Straw foam application method: Shake well, attach the straw, invert the container and begin dispensing. By activating the adapter lever carefully, the extrusion rate can be regulated.

LIMITATIONS

- This product is extremely flammable when dispensing.
- Carefully review cautions.
- Optimum temperature for use is between 65° - 80°F (18° - 27°C).
- Clean oil, dust and grease off surfaces to be foamed.
- Make sure to cover surrounding surfaces.
- Wear appropriate safety glasses, gloves and protective clothing. Consult SDS for product safety information.
- Use in Type V residential construction in vertical and horizontal penetrations between floors and rooms.
- It is NOT intended for use in hourly rated assemblies.
- Consult local building codes before use.

For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

CAUTION STATEMENT

DANGER: Extremely flammable aerosol. Contains gas under pressure and may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeat exposure. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Avoid breathing vapors or fumes. Do not get in eyes, on skin, or on clothing. Wash hands and other skin areas exposed to material thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye protection. In case of inadequate ventilation, wear respiratory protection. **FIRST AID:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove any contact lenses and continue rinsing. If irritation persists: Get medical advice or attention. **FIRE:** In case of fire: Use water fog, foam, dry chemical, or CO₂ for extinction. Eliminate all ignition sources if safe to do so. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Dispose of contents and container in accordance with applicable local, regional, national, or international regulations. For additional information, refer to Safety Data Sheet.

TITEBOND.COM



Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583 ©2020 00940-4736LN FF1036

